

2.0 mm | 6 Mil
TRAVANE™
GLUE DOWN

6 x 48 WOOD LOOK PLANKS



GOLDEN OAK TV35



NATURAL TV30



BIRCH WHITE TV32



WHEATWOOD TV31



WEATHERED PINE TV33



WALNUT TV34

2.0 mm | 6 Mil
TRAVANE™
GLUE DOWN



DESIGN & SIZE

Product Type:	Glue Down LVF
Thickness:	2.0 mm
Wear Layer:	6 Mil (0.1524 mm)
Finish:	Polyurethane protective coating
Size (nominal):	6" W x 48" L Plank
Size (actual):	152.4 mm x 1219.2 mm
Packaging:	54 sq. ft. per carton 27 pieces per carton
Weight:	1.35 lbs per piece 37.7 lbs per carton
Installation & Adhesive:	Glue down and install using ProSeries by Daltile Adhesive; see daltile.com/LVF for more recommended installation and adhesive information

SERVICE

Warranty:	Limited 15 Year Residential
-----------	-----------------------------

PERFORMANCE

Construction:	Residential Grade Luxury Vinyl Flooring; 100% Virgin
Classification:	ASTM F1700 - Class III, Type A - Smooth, Type B - Embossed
Squareness:	ASTM F2421 - Passes - ± 0.010 " max
Size and Tolerance:	ASTM F2421 - Passes - ± 0.016 in. / linear foot
Thickness:	ASTM F386 - Passes - as specified ± 0.005 in
Flexibility:	ASTM F137 - Passes - 1" mandrel
Dimensional Stability:	ASTM F2199 - Passes - 0.020 in. / linear foot max
Static Load Limit:	ASTM F970 - Passes, modified at 1000 psi
Residual Indentation:	ASTM F1914 - Passes - Average less than 8% maximum single reading 10%
Resistance To Chemicals:	ASTM F925 - Passes - No more than a slight change
Resistance To Light:	ASTM F1515 - Passes - $\Delta E \leq 8$
Resistance To Heat:	ASTM F1514 - Passes - $\Delta E \leq 8$
Critical Radiant Flux:	ASTM E648 - Class 1 (> 0.45 W/cm ²)
Smoke Density:	ASTM E662 Part A - Passes - < 450



7834 C.F. Hawn Freeway,
Dallas, Texas 75217 | 1.800.933.TILE

To view the complete collection of
Daltile® products and information,
visit our website at daltile.com/LVF



©2020 Dal-Tile Corporation (09/20)